



EPS Sandwich Panel - Specification





Steel skin(Top and Bottom)	PPGI (Pre Painted Galvanized Steel sheet)
Core	EPS(Expanded polystyrene), Density 8kg/m ³ -20kg/m ³
Steel skin thickness	0.4mm-0.8mm
Core thickness	50/75/100/150/200mm
Width	950/1150mm
Length	Less than 11.8m
Color	Customized
Service life	25 years
Advantage	Heat Insulation, Light weighted

Rock Wool Sandwich Panel - Specification



Steel skin(Top and Bottom)	PPGI (Pre Painted Galvanized Steel sheet)
Core	Rock wool, Density: 60kg/m ³ -180kg/m ³
Steel skin thickness	0.4mm-0.8mm
Core thickness	50/75/100/150/200mm
Width	950/1150mm
Length	Less than 11.8m
Color	Customized
Fire-proofing Grade	Grade A
Service life	25 years
Advantage	Heat Insulation, Fire-proofing, Sound-proofing

PU(Polyurethane) Sandwich Panel - Specification



Steel skin(Top and Bottom)	PPGI (Pre Painted Galvanized Steel sheet)
Core	PU(Polyurethane), Density: 38kg/m ³ -45kg/m ³
Steel skin thickness	0.4mm-0.8mm
Core thickness	50/75/100//150/200mm
Width	1000mm
Length	Less than 11.8m
Color	Customized
Fire-proofing Grade	Grade B1, B2
Service life	25 years
Advantage	Heat Insulation, Fireproofing,